

## FlowGT R180F

Effective measurement of corrosive liquids & gases for high pressure with lining

Temperature Range

**-20 Deg to 90 Deg Celcius**

Pressure Range

**0 to 5 Bar**

Accuracy

**+/-2% of FSD**

### 1. Process Range & Limitations

| Parameter           | Specification             |
|---------------------|---------------------------|
| Measuring Principle | Variable Area (Rotameter) |
| Temperature Range   | -20 Deg to 90 Deg Celcius |
| Pressure Range      | 0 to 5 Bar                |
| Accuracy            | +/-2% of FSD              |
| F / F Height        | 500 +/- 5 mm              |
| Scale Length        | 180 - 200 mm Approx       |

### 2. Fixed Technical Specifications

| Parameter               | Specification       |
|-------------------------|---------------------|
| Gland Packing           | PTFE + Neoprene     |
| Glass Tube              | Borosilicate Glass  |
| Protection Cover        | Transparent Acrylic |
| End Connection MOC      | MS                  |
| Process Connection Type | Flange End          |
| Process Connection MOC  | MS                  |
| Process Connection Std  | ASA 150 # RF        |
| Float MOC               | SS 316              |
| Float Retainer          | SS 316              |
| Scale MOC               | Acrylic             |
| Body MOC                | MS+Powder Coated    |
| Inlet / Outlet          | Bottom / Top        |

### 3. Variable Technical Specifications

| Code                           | Description               |
|--------------------------------|---------------------------|
| <b>PROCESS CONNECTION TYPE</b> |                           |
| F                              | Flange-End                |
| T                              | Threaded                  |
| T1                             | TC-Connection             |
| Cu                             | Custom Type: Mention Type |
| <b>PROCESS CONNECTION STD</b>  |                           |
| F2                             | ASA 300                   |
| TB1                            | BSP (M)                   |
| TN1                            | NPT (M)                   |
| Cu                             | Custom Std: Mention Std   |
| <b>INLET/OUTLET</b>            |                           |
| BT                             | Bottom/Top                |
| CU                             | Cust.(Mention)            |

### Model De-Codification

FM IPL - GTRM - WP - C - FS - RS - SA1 - BP - xx - xx - xx - NB

Flowtech Measuring Instruments Pvt. Ltd. | Glass Tube Rotameter Technical Datasheet | FlowGT R180F

Specifications subject to change without notice. For ordering, please refer to the model de-codification code.