

FlowGT R270F
Effective measurement of corrosive liquids & gases for high pressure with lining

Temperature Range
-20 Deg to 90 Deg Celcius

Pressure Range
0 to 5 Bar

Accuracy
+/-2% of FSD
1. Process Range & Limitations

Parameter	Specification
Measuring Principle	Variable Area (Rotameter)
Temperature Range	-20 Deg to 90 Deg Celcius
Pressure Range	0 to 5 Bar
Accuracy	+/-2% of FSD
F / F Height	500 +/- 5 mm
Scale Length	180 - 200 mm Approx

2. Fixed Technical Specifications

Parameter	Specification
Gland Packing	PTFE + Neoprene
Glass Tube	Borosilicate Glass
Protection Cover	Transparent Acrylic
End Connection MOC	SS 304
Process Connection Type	Flange End
Process Connection MOC	SS 304
Process Connection Std	ASA 150 # RF
Float MOC	SS 316
Float Retainer	SS 316
Scale MOC	SS 304
Body MOC	SS 304
Inlet / Outlet	Bottom / Top

3. Variable Technical Specifications

Code	Description
PROCESS CONNECTION TYPE	
F	Flange-End
T	Threaded
T1	TC-Connection
Cu	Custom Type: Mention Type
PROCESS CONNECTION STD	
F2	ASA 300
TB1	BSP (M)
TN1	NPT (M)
Cu	Custom Std: Mention Std
INLET/OUTLET	
BT	Bottom/Top
CU	Cust.(Mention)

Model De-Codification
FM IPL - GTRM - WP1 - S1 - FS - RS - SS - BS - xx - xx - xx - NB

Flowtech Measuring Instruments Pvt. Ltd. | Glass Tube Rotameter Technical Datasheet | FlowGT R270F
 Specifications subject to change without notice. For ordering, please refer to the model de-codification code.