

FlowGT RP180

Cost-Effective measurement of corrosive liquids & gases

Temperature Range

-20 Deg to 90 Deg Celcius

Pressure Range

0 to 5 Bar

Accuracy

+/-2% of FSD

1. Process Range & Limitations

Parameter	Specification
Measuring Principle	Variable Area (Rotameter)
Temperature Range	-20 Deg to 90 Deg Celcius
Pressure Range	0 to 5 Bar
Accuracy	+/-2% of FSD
F / F Height	500 +/- 5 mm
Scale Length	180 - 200 mm Approx

2. Fixed Technical Specifications

Parameter	Specification
Gland Packing	PTFE + Neoprene
Glass Tube	Borosilicate Glass
Protection Cover	Transparent Acrylic
End Connection MOC	PP
Process Connection Type	Flange End
Process Connection MOC	PP
Process Connection Std	ASA 150 # RF
Float MOC	Teflon
Float Retainer	Teflon
Scale MOC	Acrylic
Body MOC	MS + Powder Coated
Inlet / Outlet	Bottom / Top

3. Variable Technical Specifications

Code	Description
BODY MOC	
BP	MS+Powder Coated - Default
BF	MS+FRP Coating
INLET/OUTLET	
BT	Bottom/Top
CU	Cust.(Mention)

Model De-Codification

FMIPL - GTRM - WP3 - F - P1 - F1 - FT - RT - SA1 - xx - xx - NB