



FlowMag S630B

For simple water and process applications

FMIPL-EMFM-TS1-F-C-F1-CH1-EL2-ER-PL-WP-W2-M-CR-BT-XX-XX-CG1-CE2-CP1-NB

1. PROCESS RANGE & LIMITATIONS

Parameter	Specification
Temperature Range	-10 Deg Celcius to 100 Deg Celcius
Pressure Range	0 to 15 Kg/Cm2
Viscosity Range	Upto 3 Cp
Conductivity	Min. 5 µ S/Cm

2. FIXED TECHNICAL SPECIFICATIONS

Parameter	Specification
Tag No.	
Existing Pipe MOC	Pls. Specify
FLOWTUBE MOC	
TS1	SS 304
PROCESS CONNECTION TYPE	
F	Flanged ANSI
PROCESS CONNECTION MOC	
C	Carbon Steel
PROCESS CONNECTION STD.	
F1	ASA 150#
COIL HOUSING MOC	
CH1	CS
ELECTRODE MATERIAL	
EL 2	SS 316L
EARTHING TYPE	
ER	Earthing Ring - SS 304 MOC
LININIG MATERIAL	
PL	PTFE
ELECTRONICS ENCLOSURE	
WP	Weather Proof Aluminium Die Cast
WIRING TYPE	
W2	4-Wire
OUTPUT	
M	4-20 mA+Pulse
COMMUNICATION	
CR	RS 485
POWER SUPPLY	
BT	Battery Operated - 3.5V Lithium Battery

3. VARIABLE TECHNICAL SPECIFICATIONS

Parameter	Options	Std
TRANSMITTER MOUNTING		
I	Integral Type	Y
RE	Remote Type	Y
Wire Length		
ACCESSORIES		
FP	FRP Panel	Y
MF	Matching Flanges	Y
GN	Gasket & Nut Bolts	N
NA	Not Applicable	Y
CABLE GLAND MOC		
CG1	SS 304	Y
CABLE ENTRY STANDARD		
CE2	PG 11	Y
CABLE GLAND PROTECTION		
CP1	Weather-Proof	Y

OTHER DETAILS

Branding	Flowtech
Acuracy	+/-0.5% of FSD
Packing	Wooden / Other
SPECIAL REMARKS	