



FlowMag S900

For demanding wastewater & process applications



1. PROCESS RANGE & LIMITATIONS

Parameter	Specification
Temperature Range	-10 Deg Celcius to 100 Deg Celcius
Pressure Range	0 to 25 Kg/Cm2
Viscosity Range	Upto 3 Cp
Conductivity	Min. 5 µ S/Cm
Corrosion	Suitable for Highly Corrosive Liquids like wastewater and chemicals

2. FIXED TECHNICAL SPECIFICATIONS

Parameter	Specification
Tag No.	
Existing Pipe MOC	Pls. Specify
FLOWTUBE MOC	
TS1	SS 316
PROCESS CONNECTION TYPE	
F	Flanged ANSI
PROCESS CONNECTION MOC	
C	Carbon Steel
PROCESS CONNECTION STD.	
F1	ASA 150#
COIL HOUSING MOC	
CH2	SS 304
EARTHING TYPE	
ER	Earthing Ring
EARTHING RING MOC	
ER1	SS 304
LININIG MATERIAL	
PL	PTFE
WIRING TYPE	
W2	4-Wire
ELECTRONICS ENCLOSURE	
WP	Weather Proof Aluminium Die Cast
COMMUNICATION	
CR	RS 485
CABLE GLAND MOC	
CG1	SS 304
CABLE ENTRY STANDARD	
CE2	PG 11
CABLE GLAND PROTECTION	
CP1	Weather-Proof

3. VARIABLE TECHNICAL SPECIFICATIONS

Parameter	Options	Std
OUTPUT		
M	4-20 mA+Pulse	Y
H	4-20mA + HART + Pulse	Y
ELECTRODE MATERIAL		4 Nos
EL 3	Hastalloy - C	Y
EL 4	Tantalum	Y
TRANSMITTER MOUNTING		
I	Integral Type	Y
RE	Remote Type	Y
Wire Length		
POWER SUPPLY		
AC 1	230 V AC - Default	Y
DC	24 V DC	Y
AC 2	110 V AC	Y
ACCESSORIES		
FP	FRP Panel	Y
MF	Matching Flanges	Y
GN	Gasket & Nut Bolts	N
NA	Not Applicable	Y

OTHER DETAILS

Branding	Flowtech
Acuracy	+/-0.5% of FSD
Packing	Wooden / Other
SPECIAL REMARKS	