



FlowMag S900F: Electromagnetic Flowmeter

FM1PL-EMFM-TS1-C-CH2-ER-ER1-PL-W2-WP-CR-CG1-CE2-CP1-M-XX-XX-XX-XX-XX-NB

1. PROCESS RANGE & LIMITATIONS

Parameter	Specification
Temperature Range	-10 Deg Celcius to 100 Deg Celcius
Pressure Range	0 to 200 Kg/Cm2
Viscosity Range	Upto 3 Cp
Conductivity	Min. 5 µ S/Cm
Corrosion	Suitable for Highly Corrosive Liquids like wastewater and chemicals

2. FIXED TECHNICAL SPECIFICATIONS

Parameter	Specification
Tag No.	
Existing Pipe MOC	Pls. Specify
FLOWTUBE MOC	
TS1	SS 316
PROCESS CONNECTION MOC	
C	Carbon Steel
COIL HOUSING MOC	
CH2	SS 304
EARTHING TYPE	
ER	Earthing Ring
EARTHING RING MOC	
ER1	SS 304
LININIG MATERIAL	
PL	PTFE
WIRING TYPE	
W2	4-Wire
ELECTRONICS ENCLOSURE	
WP	Weather Proof Aluminium Die Cast
COMMUNICATION	
CR	RS 485
CABLE GLAND MOC	
CG1	SS 304
CABLE ENTRY STANDARD	
CE2	PG 11
CABLE GLAND PROTECTION	
CP1	Weather-Proof

3. VARIABLE TECHNICAL SPECIFICATIONS

Parameter	Options	Std
OUTPUT		
M	4-20 mA+Pulse	Y
H	4-20mA + HART + Pulse	Y
ELECTRODE MATERIAL		
EL 3	Hastalloy - C	Y
EL 4	Tantalum	Y
TRANSMITTER MOUNTING		
I	Integral Type	Y
RE	Remote Type	Y
Wire Length		
POWER SUPPLY		
AC 1	230 V AC - Default	Y
DC	24 V DC	Y
AC 2	110 V AC	Y
PROCESS CONNECTION TYPE		
F	Flange-End	Y
T	Threaded	Y
Cu	Custom Std: Mention Std	Y
PROCESS CONNECTION STD		
F2	ASA 300	Y
F3	ASA 600	Y
T1	NPT	Y
ACCESSORIES		
FP	FRP Panel	Y
MF	Matching Flanges	Y
GN	Gasket & Nut Bolts	N
NA	Not Applicable	Y
OTHER DETAILS		
Branding	Flowtech	
Acuracy	+/-0.5% of FSD	
Packing	Wooden / Other	
SPECIAL REMARKS		