

FlowMag S90: PVC Electromagnetic Flowmeter

For simple water and process applications

FM1PL-EMFM-Cu-F-Cu-F1-Cu-ER-IF-WP-W2-M-CR-CG1-CP1-XX-XX-NB

1. PROCESS RANGE & LIMITATIONS

Parameter	Specification
Temperature Range	-10 Deg Celcius to 60 Deg Celcius
Pressure Range	0 to 15 Kg/Cm2
Viscosity Range	Upto 3 Cp
Conductivity	Min. 5 µ S/Cm

2. FIXED TECHNICAL SPECIFICATIONS

Parameter	Specification
Tag No.	
Existing Pipe MOC	Pls. Specify
FLOWTUBE MOC	
C	Custom MOC: CPVC
PROCESS CONNECTION TYPE	
F	Flange-End
PROCESS CONNECTION MOC	
Cu	Custom MOC: CPVC
PROCESS CONNECTION STD.	
F1	ASA 150 Class
COIL HOUSING MOC	
ELECTRODE MATERIAL	
EL 2	SS 316L
EARTHING TYPE	
ER	Earthing Ring: SS 316
LININIG MATERIAL	
ELECTRONICS ENCLOSURE	
WP	Weather Proof Aluminium Die Cast
WIRING TYPE	
W2	4-Wire
OUTPUT	
M	4-20 mA+Pulse
COMMUNICATION	
CR	RS 485
CABLE GLAND MOC	
CG1	SS 304
CABLE ENTRY STANDARD	
CE2	PG 11
CABLE GLAND PROTECTION	
CP1	Weather-Proof

3. VARIABLE TECHNICAL SPECIFICATIONS

Parameter	Options	Std
TRANSMITTER MOUNTING		
I	Integral Type	Y
RE	Remote Type	Y
Wire Length		
POWER SUPPLY		
AC 1	230 V AC - Default	Y
DC	24 V DC	Y
AC 2	110 V AC	Y
ACCESSORIES		
FP	FRP Panel	Y
MF	Matching Flanges	Y
GN	Gasket & Nut Bolts	N
NA	Not Applicable	Y

OTHER DETAILS

Branding	Flowtech
Acuracy	+/-0.5% of FSD
Packing	Wooden / Other
SPECIAL REMARKS	