



FlowMag S930

For hygiene applications in Food & Beverage Industry

FM IPL-ENFM-TS2-S2-CH3-IF-PL-W2-CR-EL2-WP-M-CG1-CE2-CP1-XX-XX-XX-XX-NB

1. PROCESS RANGE & LIMITATIONS

Parameter	Specification
Temperature Range	-10 Deg Celcius to 100 Deg Celcius
Pressure Range	0 to 15 Kg/Cm2
Viscosity Range	Upto 3 Cp
Conductivity	Min. 5 µ S/Cm

2. FIXED TECHNICAL SPECIFICATIONS

Parameter	Specification
Tag No.	
Existing Pipe MOC	Pls. Specify
FLOWTUBE MOC	
TS2	SS 316
PROCESS CONNECTION MOC	
S2	SS 316
COIL HOUSING MOC	
CH3	SS 316
EARTHING TYPE	
IF	In-built Earthing Electrode
LININIG MATERIAL	
PL	PTFE
WIRING TYPE	
W2	4-Wire
COMMUNICATION	
CR	RS 485
ELECTRODE MATERIAL	
EL 2	SS 316L
ELECTRONICS ENCLOSURE	
WP	Weather Proof Aluminium Die Cast
OUTPUT	
M	4-20 mA+Pulse
CABLE GLAND MOC	
CG1	SS 316
CABLE ENTRY STANDARD	
CE2	PG 11
CABLE GLAND PROTECTION	
CP1	Weather-Proof

3. VARIABLE TECHNICAL SPECIFICATIONS

Parameter	Options	Std
PROCESS CONNECTION TYPE		
F	Flanged ANSI - Default	Y
TC	Tri-Clover Connection	Y
PROCESS CONNECTION STD.		
F1	ASA 150# - Only in Flange Connection	Y
Cu	Custom Std: Mention Std	Y
TRANSMITTER MOUNTING		
I	Integral Type	Y
RE	Remote Type	Y
Wire Length		
POWER SUPPLY		
AC 1	230 V AC - Default	Y
DC	24 V DC	Y
AC 2	110 V AC	Y
ACCESSORIES		
FP	FRP Panel	Y
MF	Matching Flanges	Y
GN	Gasket & Nut Bolts	N
NA	Not Applicable	Y

OTHER DETAILS

Branding	Flowtech
Acuracy	+/-0.5% of FSD
Packing	Wooden / Other
SPECIAL REMARKS	