

FlowMet L180F

For high pressure measurement of standard liquid and gas applications

Temperature Range -30 Deg Celcius to 350 Deg Celcius	Pressure Range -0.9 Bar to 200 Bar	Accuracy +/- 2% FSD	Turndown 01:10:00
---	---------------------------------------	------------------------	----------------------

1. Process Range & Limitations

Parameter	Specification
Measuring Principle	Variable Area (Metal Tube Rotameter)
Temperature Range	-30 Deg Celcius to 350 Deg Celcius
Pressure Range	-0.9 Bar to 200 Bar
Turndown Ratio	01:10:00
Accuracy	+/- 2% FSD
Installation	Vertical Installation
F / F Length	250 MM (+/- 10MM)

2. Fixed Technical Specifications

Parameter	Specification
Protection Cover	Transparent Acrylic / Glass
Wetted Parts MOC	SS 316
Flow Tube MOC	SS 316
Process Connection Type	Flange End
Process Connection MOC	SS 316
Process Connection Std	ASA 150 # RF
Float MOC	SS 316
Float Retainer	SS 316
Scale MOC	Aluminium
Liner MOC	Not Applicable
Jacketing	Jacketing Not Applicable
Enclosure MOC	Aluminium
Enclosure Protection	Weatherproof
Digital / Analogue	Analogue
Cable Gland MOC	SS 304
Cable Gland Std	PG 9
Cable Gland Protection	Weather-Proof

3. Variable Technical Specifications

Code	Description
PROCESS CONNECTION TYPE	
F	Flange-End
T	Threaded
Cu	Custom Type
PROCESS CONNECTION STD	
F1	ASA 300
TB1	BSP (M)
Cu	Custom Std: Mention Std

Model De-Codification

FLIPM-MTRM-WP2-TS2-S2-FS-RS-JNA-SA-NA-EA-WP-AG-VI-FF2-CG1-CS1-CGP1-xx-xx-NB