

FlowMet L600

For measurement of Highly Corrosive Applications

Temperature Range -30 Deg Celcius to 150 Deg Celcius	Pressure Range -0.9 Bar to 40 Bar	Accuracy +/- 2% FSD	Turndown 01:10:00
---	--------------------------------------	------------------------	----------------------

1. Process Range & Limitations

Parameter	Specification
Measuring Principle	Variable Area (Metal Tube Rotameter)
Temperature Range	-30 Deg Celcius to 150 Deg Celcius
Pressure Range	-0.9 Bar to 40 Bar
Turndown Ratio	01:10:00
Accuracy	+/- 2% FSD
Installation	Vertical Installation
F / F Length	250 MM (+/- 10MM)

2. Fixed Technical Specifications

Parameter	Specification
Protection Cover	Transparent Acrylic / Glass
Wetted Parts MOC	Weatherproof
Flow Tube MOC	SS 316
Process Connection Type	Flange End
Process Connection MOC	SS 316
Process Connection Std	ASA 150 # RF
Float MOC	SS 316 + PTFE Coating
Float Retainer	Teflon
Scale MOC	Aluminium
Liner MOC	PTFE Lining
Jacketing	Not Applicable
Enclosure MOC	Aluminium
Enclosure Protection	Weatherproof
Digital / Analogue	Analogue
Cable Gland MOC	SS 304
Cable Gland Std	PG 9
Cable Gland Protection	Weather-Proof: Applicable with Weatherproof Enclosure

Model De-Codification

FM IPL - MTRM - TS2 - F - S2 - F1 - FT - RT - SA - PL - EA - VI - FF2 - CG1 - CS1 - AG - WP - CGP1 - NB
