

FlowMet L630F

For measurement of Highly Corrosive Applications with High Pressure

Temperature Range -30 Deg Celcius to 150 Deg Celcius	Pressure Range -0.9 Bar to 400 Bar	Accuracy +/- 2% FSD	Turndown 01:10:00
---	---------------------------------------	------------------------	----------------------

1. Process Range & Limitations

Parameter	Specification
Measuring Principle	Variable Area (Metal Tube Rotameter)
Temperature Range	-30 Deg Celcius to 150 Deg Celcius
Pressure Range	-0.9 Bar to 400 Bar
Turndown Ratio	01:10:00
Accuracy	+/- 2% FSD
Installation	Vertical Installation
F / F Length	250 MM (+/- 10MM)

2. Fixed Technical Specifications

Parameter	Specification
Protection Cover	Transparent Acrylic / Glass
Wetted Parts MOC	Weatherproof
Flow Tube MOC	SS 316
Process Connection Type	Flange End
Process Connection MOC	SS 316
Process Connection Std	ASA 150 # RF
Float MOC	SS 316 + PTFE Coating
Float Retainer	Teflon
Scale MOC	Aluminium
Liner MOC	PTFE Lining
Jacketing	Not Applicable
Enclosure MOC	Aluminium
Enclosure Protection	Weatherproof
Digital / Analogue	Digital Output: 4-20mA + HART
Cable Gland MOC	SS 304
Cable Gland Std	PG 9
Cable Gland Protection	Weather-Proof: Applicable with Weatherproof Enclosure

3. Variable Technical Specifications

Code	Description
PROCESS CONNECTION TYPE	
F	Flange-End
T	Threaded
Cu	Custom Type: Mention Type
PROCESS CONNECTION STD	
F1	ASA 300
F2	ASA 600
TB1	BSP (M)
TB2	NPT (M)
Cu	Custom Std: Mention Std

Model De-Codification

FMIPL - MTRM - TS2 - S2 - FT - RT - SA - PL - EA - VI - FF2 - CG1 - CS1 - DG - WP - CGP1 - xx - xx - NB
