

FlowMet L900

For specialised measurement in Hygiene & Foog Grade Applications

Temperature Range -30 Deg Celcius to 150 Deg Celcius	Pressure Range -0.9 Bar to 40 Bar	Accuracy +/- 2% FSD	Turndown 01:10:00
---	--------------------------------------	------------------------	----------------------

1. Process Range & Limitations

Parameter	Specification
Measuring Principle	Variable Area (Metal Tube Rotameter)
Temperature Range	-30 Deg Celcius to 150 Deg Celcius
Pressure Range	-0.9 Bar to 40 Bar
Turndown Ratio	01:10:00
Accuracy	+/- 2% FSD
Installation	Vertical Installation
F / F Length	250 MM (+/- 10MM)

2. Fixed Technical Specifications

Parameter	Specification
Protection Cover	Transparent Acrylic / Glass
Wetted Parts MOC	SS 316
Flow Tube MOC	SS 316
Process Connection Type	Flange End
Process Connection MOC	SS 316
Process Connection Std	ASA 150 # RF
Float MOC	SS 316
Float Retainer	SS 316
Scale MOC	Aluminium
Liner MOC	Not Applicable
Jacketing	Not Applicable
Enclosure MOC	Aluminium
Enclosure Protection	Weatherproof
Digital / Analogue	Analogue
Cable Gland MOC	SS 304
Cable Gland Std	PG 9
Cable Gland Protection	Weather-Proof: Applicable with Weatherproof Enclosure

3. Variable Technical Specifications

Code	Description
DIGITAL/ANALOGUE	
AG	Analogue
DG	Digital: 4-20 mA + HART Output
PROCESS CONNECTION TYPE	
F	Flange-End: ASA 150 Class
T	TC Joint

Model De-Codification

FMIPL -MTRM-WP2-TS2-S2-FS-RS-SA-NA-EA-WP-VI-FF2-CG1-CS1-CGP1-xx-xx-NB
