



FlowRLG L180F: Reflex Level Gauge			
1. PROCESS RANGE & LIMITATIONS			
Parameter		Specification	
2. FIXED TECHNICAL SPECIFICATIONS			
Parameter		Specification	
Tag No.			
C/C Height			
MAIN CHAMBER MOC			
MC4		PP with CS Plate	
MAIN CHAMBER SIZE			
42		40 X 40	
COVER PLATE MOC			
CP4		PP	
PROCESS CONNECTION MOC			
P		PP	
U-BOLTS & NUTS MOC			
UN4		Aluminium	
3. VARIABLE TECHNICAL SPECIFICATIONS			
Parameter		Options	Std
PROCESS CONNECTION TYPE			
F		Flange End	Y
T		Threaded	Y
CU		Cust.	Y
PROCESS CONNECTION STD			
F1		ASA 150 # RF	Y
F2		ASA 300 #RF	Y
F3		ASA 600 #RF	Y
TB		1/2" TO 2" BSP	Y
TN		1/2" TO 2" NPT	Y
SCALE MOC		Required / Not Required	Y
AL		Aluminium	N
SS		SS 304	Y
SS1		SS 316	Y
GLASS DETAILS			
GD1		Indian Make Borosilicate Toughened Glass	Y
GD2		Imported Toughened Glass	Y
GD3		Klinger Make Toughened Glass	Y
OTHER DETAILS			
U Bolts & Nuts Standard		ASTM A193Gr.B7 & ASTM A194 Class 2H.	
Sealing Gasket MOC		PTFE	
Cushion Gasket MOC		PTFE	
Hydro Test (Max.)		Op. Press. X 2	
Max Temp		80 Deg C for PP	
Air Vent		½"BSP Stop Plug: MOC will be same as Chamber MOC	
Drain		1. 1/2" BSP Stop Plug - MOC same as Chamber MOC	
Branding		Flowtech	
Packing		Wooden / Other	