

Flowtech Measuring Instruments Pvt. Ltd.

ISO 9001:2015 Certified

FlowRLG L180V: Reflex Level Gauge

FlowRLG L180V: Reflex Level Gauge

1. PROCESS RANGE & LIMITATIONS		
Parameter	Specification	
2. FIXED TECHNICAL SPECIFICATIONS		
Parameter	Specification	
Tag No.		
C/C Height		
MAIN CHAMBER MOC		
MC4	PP	
MAIN CHAMBER SIZE		
42	40 X 40	
COVER PLATE MOC		
CP4	PP	
PROCESS CONNECTION TYPE		
F	Flange End	
PROCESS CONNECTION MOC		
P	PP	
PROCESS CONNECTION STD		
F1	ASA 150 # RF	
ISOLATION VALVE		
W	With - PP Inbuilt Needle Valve	
VALVE MOC		
VM4	PP	
Valve Trim MOC		
VT4	PP	
Handle Details	CI Handle	
U-BOLTS & NUTS MOC		
UN4	Aluminium	
3. VARIABLE TECHNICAL SPECIFICATIONS		
Parameter	Options	Std
SCALE MOC	Required / Not Required	Y
AL	Aluminium	N
SS	SS 304	Y
SS1	SS 316	Y
GLASS DETAILS		
GD1	Indian Make Borosilicate Toughened Glass	Y
GD2	Imported Toughened Glass	Y
GD3	Klinger Make Toughened Glass	Y
OTHER DETAILS		
U Bolts & Nuts Standard	ASTM A193Gr.B7 & ASTM A194 Class 2H.	
Sealing Gasket MOC	PTFE	
Cushion Gasket MOC	PTFE	
Hydro Test (Max.)	Op. Press. X 2	
Max Temp	80 Deg C for PP	
Air Vent	½"BSP Stop Plug: MOC will be same as Chamber MOC	
Drain	1. 1/2" BSP Stop Plug - MOC same as Chamber MOC	
Branding	Flowtech	
Packing	Wooden / Other	

Technical Datasheet Rev.01

Page 1/1

Flowtech Measuring Instruments Pvt. Ltd.