



FlowRLG L270F: Reflex level Gauge		
1. PROCESS RANGE & LIMITATIONS		
Parameter		Specification
2. FIXED TECHNICAL SPECIFICATIONS		
Parameter		Specification
Tag No.		
C/C Height		
MAIN CHAMBER MOC		
MC		CS
COVER PLATE MOC		
CP1		CS
PROCESS CONNECTION MOC		
C		CS
ISOLATION VALVE		
WO		Without
Handle Details		CI Handle
U-BOLTS & NUTS MOC		
UN1		CS
3. VARIABLE TECHNICAL SPECIFICATIONS		
Parameter		Options
		Std
PROCESS CONNECTION TYPE		
F		Flange End
T		Threaded
CU		Cust.
PROCESS CONNECTION STD		
F1		ASA 150 # RF
F2		ASA 300 #RF
F3		ASA 600 #RF
TB		1/2" TO 2" BSP
TN		1/2" TO 2" NPT
MAIN CHAMBER SIZE		
38		38 X 38: For Pressure Upto 50 Bar
45		45 X 45: For Pressure Above 50 Bar
SCALE MOC		
		Required / Not Required
AL		Aluminium
SS		SS 304
SS1		SS 316
GLASS DETAILS		
GD1		Indian Make Borosilicate Toughened Glass
GD2		Imported Toughened Glass
GD3		Klinger Make Toughened Glass
OTHER DETAILS		
U Bolts & Nuts Standard		ASTM A193Gr.B7 & ASTM A194 Class 2H.
Sealing Gasket MOC		CAF
Cushion Gasket MOC		CAF
Hydro Test (Max.)		Op. Press. X 2
Max Temp		300° C for MS
Air Vent		½"BSP Stop Plug: MOC will be same as Chamber MOC
Drain		1. 1/2" BSP Stop Plug - MOC same as Chamber MOC
Branding		Flowtech
Packing		Wooden / Other