



FlowRLG L360F: Reflex level Gauge

1. PROCESS RANGE & LIMITATIONS

Parameter	Specification
-----------	---------------

2. FIXED TECHNICAL SPECIFICATIONS

Parameter	Specification
Tag No.	
C/C Height	
MAIN CHAMBER MOC	
MC1	SS 304
PROCESS CONNECTION MOC	
S1	SS 304
ISOLATION VALVE	
WO	Without
Handle Details	CI Handle

3. VARIABLE TECHNICAL SPECIFICATIONS

Parameter	Options	Std
COVER PLATE MOC		
CP2	SS 304	Y
CS	CS	Y
PROCESS CONNECTION TYPE		
F	Flange End	Y
T	Threaded	Y
CU	Cust.	Y
PROCESS CONNECTION STD		
F1	ASA 150 # RF	Y
F2	ASA 300 #RF	Y
F3	ASA 600 #RF	Y
TB	1/2" TO 2" BSP	Y
TN	1/2" TO 2" NPT	Y
MAIN CHAMBER SIZE		
38	38 X 38: For Pressure Upto 50 Bar	Y
45	45 X 45: For Pressure Above 50 Bar	Y
SCALE MOC		
	Required / Not Required	Y
AL	Aluminium	N
SS	SS 304	Y
SS1	SS 316	Y
GLASS DETAILS		
GD1	Indian Make Borosilicate Toughened Glass	Y
GD2	Imported Toughened Glass	Y
GD3	Klinger Make Toughened Glass	Y
U-BOLTS & NUTS MOC		
UN1	CS	Y
UN2	SS 304	Y
OTHER DETAILS		
U Bolts & Nuts Standard	ASTM A193Gr.B7 & ASTM A194 Class 2H.	
Sealing Gasket MOC	SS with Grafoil	
Cushion Gasket MOC	SS with Grafoil	
Hydro Test (Max.)	Op. Press. X 2	
Max Temp	300° C for SS	
Air Vent	½"BSP Stop Plug: MOC will be same as Chamber MOC	
Drain	1. 1/2" BSP Stop Plug - MOC same as Chamber MOC	
Branding	Flowtech	
Packing	Wooden / Other	