



FlowRLG L360FV: Reflex Level Gauge			
1. PROCESS RANGE & LIMITATIONS			
Parameter		Specification	
2. FIXED TECHNICAL SPECIFICATIONS			
Parameter		Specification	
Tag No.			
C/C Height			
MAIN CHAMBER MOC			
MC1		SS 304	
PROCESS CONNECTION MOC			
S1		SS 304	
ISOLATION VALVE			
W		With	
VALVE MOC			
VM2		SS 304	
VALVE TRIM MOC			
VT2		SS 304	
Handle Details		CI Handle	
3. VARIABLE TECHNICAL SPECIFICATIONS			
Parameter		Options	Std
COVER PLATE MOC			
CS		CS	Y
CP2		SS 304	Y
PROCESS CONNECTION TYPE			
F		Flange End	Y
T		Threaded	Y
CU		Cust.	Y
PROCESS CONNECTION STD			
F1		ASA 150 # RF	Y
F2		ASA 300 #RF	Y
F3		ASA 600 #RF	Y
TB		1/2" TO 2" BSP	Y
TN		1/2" TO 2" NPT	Y
MAIN CHAMBER SIZE			
38		38 X 38: For Pressure Upto 50 Bar	Y
45		45 X 45: For Pressure Above 50 Bar	Y
VALVE DETAILS			
VT1		In built Horizontal Needle Valve - Default	Y
VT2		Integral Auto Shut-Off Ball Check Valves	N
SCALE MOC		Required / Not Required	Y
AL		Aluminium	N
SS		SS 304	Y
SS1		SS 316	Y
GLASS DETAILS			
GD1		Indian Make Borosilicate Toughened Glass	Y
GD2		Imported Toughened Glass	Y
GD3		Klinger Make Toughened Glass	Y
U-BOLTS & NUTS MOC			
UN1		CS	Y
UN2		SS 304	Y
OTHER DETAILS			
U Bolts & Nuts Standard		ASTM A193Gr.B7 & ASTM A194 Class 2H.	
Sealing Gasket MOC		SS with Grafoil	
Cushion Gasket MOC		SS with Grafoil	
Hydro Test (Max.)		Op. Press. X 2	
Max Temp		300° C for SS	
Air Vent		½"BSP Stop Plug: MOC will be same as Chamber MOC	
Drain		1. 1/2" BSP Stop Plug - MOC same as Chamber MOC	
Branding		Flowtech	
Packing		Wooden / Other	