



FlowRLG L450F: Reflex level Gauge		
1. PROCESS RANGE & LIMITATIONS		
Parameter		Specification
2. FIXED TECHNICAL SPECIFICATIONS		
Parameter		Specification
Tag No.		
C/C Height		
MAIN CHAMBER MOC		
MC2	SS 316	
PROCESS CONNECTION MOC		
S2	SS 316	
ISOLATION VALVE		
WO	Without	
Handle Details	CI Handle	
3. VARIABLE TECHNICAL SPECIFICATIONS		
Parameter	Options	Std
COVER PLATE MOC		
CS	CS	Y
CP2	SS 304	Y
CP3	SS 316	Y
PROCESS CONNECTION TYPE		
F	Flange End	Y
T	Threaded	Y
CU	Cust.	Y
PROCESS CONNECTION STD		
F1	ASA 150 # RF	Y
F2	ASA 300 #RF	Y
F3	ASA 600 #RF	Y
TB	1/2" TO 2" BSP	Y
TN	1/2" TO 2" NPT	Y
MAIN CHAMBER SIZE		
38	38 X 38: For Pressure Upto 50 Bar	Y
45	45 X 45: For Pressure Above 50 Bar	Y
SCALE MOC		
AL	Aluminium	N
SS	SS 304	Y
SS1	SS 316	Y
GLASS DETAILS		
GD1	Indian Make Borosilicate Toughened Glass	Y
GD2	Imported Toughened Glass	Y
GD3	Klinger Make Toughened Glass	Y
OTHER DETAILS		
UN1	CS	
UN2	SS 304	
UN3	SS 316	
U Bolts & Nuts Standard	ASTM A193Gr.B7 & ASTM A194 Class 2H.	
Sealing Gasket MOC	SS with Grafoil	
Cushion Gasket MOC	SS with Grafoil	
Hydro Test (Max.)	Op. Press. X 2	
Max Temp	300° C for SS	
Air Vent	½"BSP Stop Plug: MOC will be same as Chamber MOC	
Drain	1. 1/2" BSP Stop Plug - MOC same as Chamber MOC	
Branding	Flowtech	
Packing	Wooden / Other	