



FlowRLG L450FV: Reflex Level Gauge

1. PROCESS RANGE & LIMITATIONS

Parameter	Specification
-----------	---------------

2. FIXED TECHNICAL SPECIFICATIONS

Parameter	Specification
Tag No.	
C/C Height	
MAIN CHAMBER MOC	
MC2	SS 316
PROCESS CONNECTION MOC	
S1	SS 304
ISOLATION VALVE	
W	With
VALVE MOC	
VM3	SS 316
VALVE TRIM MOC	
VT3	SS 316
Handle Details	CI Handle

3. VARIABLE TECHNICAL SPECIFICATIONS

Parameter	Options	Std
COVER PLATE MOC		
CS	CS	Y
CP2	SS 304	Y
CP3	SS 316	Y
PROCESS CONNECTION TYPE		
F	Flange End	Y
T	Threaded	Y
CU	Cust.	Y
PROCESS CONNECTION STD		
F1	ASA 150 # RF	Y
F2	ASA 300 #RF	Y
F3	ASA 600 #RF	Y
TB	1/2" TO 2" BSP	Y
TN	1/2" TO 2" NPT	Y
MAIN CHAMBER SIZE		
38	38 X 38: For Pressure Upto 50 Bar	Y
45	45 X 45: For Pressure Above 50 Bar	Y
VALVE DETAILS		
VT1	In built Horizontal Needle Valve - Default	Y
VT2	Integral Auto Shut-Off Ball Check Valves	N
SCALE MOC		
AL	Aluminium	N
SS	SS 304	Y
SS1	SS 316	Y
GLASS DETAILS		
GD1	Indian Make Borosilicate Toughened Glass	Y
GD2	Imported Toughened Glass	Y
GD3	Klinger Make Toughened Glass	Y
U-BOLTS & NUTS MOC		
UN1	CS	Y
UN2	SS 304	Y
UN3	SS 316	Y
OTHER DETAILS		
U Bolts & Nuts Standard	ASTM A193Gr.B7 & ASTM A194 Class 2H.	
Sealing Gasket MOC	SS with Grafoil	
Cushion Gasket MOC	SS with Grafoil	
Hydro Test (Max.)	Op. Press. X 2	
Max Temp	300° C for SS	
Air Vent	½"BSP Stop Plug: MOC will be same as Chamber MOC	
Drain	1. 1/2" BSP Stop Plug - MOC same as Chamber MOC	
Branding	Flowtech	
Packing	Wooden / Other	