



FlowRLG L450V: Reflex Level Gauge			
1. PROCESS RANGE & LIMITATIONS			
Parameter		Specification	
2. FIXED TECHNICAL SPECIFICATIONS			
Parameter		Specification	
Tag No.			
C/C Height			
MAIN CHAMBER MOC			
MC2	SS 316		
PROCESS CONNECTION TYPE			
F	Flange End		
PROCESS CONNECTION MOC			
S2	SS 316		
PROCESS CONNECTION STD			
F1	ASA 150 # RF		
ISOLATION VALVE			
W	With		
VALVE MOC			
VM3	SS 316		
VALVE TRIM MOC			
VT3	SS 316		
Handle Details			
		CI Handle	
3. VARIABLE TECHNICAL SPECIFICATIONS			
Parameter		Options	Std
COVER PLATE MOC			
CS	CS		Y
CP2	SS 304		Y
CP3	SS 316		Y
MAIN CHAMBER SIZE			
38	38 X 38: For Pressure Upto 50 Bar		Y
45	45 X 45: For Pressure Above 50 Bar		Y
VALVE DETAILS			
VT1	In built Horizontal Needle Valve - Default		Y
VT2	Integral Auto Shut-Off Ball Check Valves		N
SCALE MOC		Required / Not Required	Y
AL	Aluminium		N
SS	SS 304		Y
SS1	SS 316		Y
GLASS DETAILS			
GD1	Indian Make Borosilicate Toughened Glass		Y
GD2	Imported Toughened Glass		Y
GD3	Klinger Make Toughened Glass		Y
U-BOLTS & NUTS MOC			
UN1	CS		Y
UN2	SS 304		Y
UN3	SS 316		Y
OTHER DETAILS			
U Bolts & Nuts Standard		ASTM A193Gr.B7 & ASTM A194 Class 2H.	
Sealing Gasket MOC		SS with Grafoil	
Cushion Gasket MOC		SS with Grafoil	
Hydro Test (Max.)		Op. Press. X 2	
Max Temp		300° C for SS	
Air Vent		½"BSP Stop Plug: MOC will be same as Chamber MOC	
Drain		1. 1/2" BSP Stop Plug - MOC same as Chamber MOC	
Branding		Flowtech	
Packing		Wooden / Other	