



FlowSM L180: Side Mounted Magnetic Level Indicator

Cost-effective level measurement for corrosive application

FMIPL-SMMLI-F-P-F1-PC-FP-XX-XX-XX-XX-NB-MM

1. PROCESS RANGE & LIMITATIONS

Parameter	Specification
Pressure Range	1 Bar to 8 Bar
Temperature Range	10 Deg Celcius to 80 Deg Celcius

2. FIXED TECHNICAL SPECIFICATIONS

Parameter	Specification
Tag No.	
C/C Height	
Casing	Aluminium Channel 2mm Thickness
Scale	Aluminium with LC-5 / Direct Engraved on casing
PROCESS CONNECTION TYPE	
F	Flange End
PROCESS CONNECTION MOC	
P	PP
PROCESS CONNECTION STD	
F1	ASA 150 # RF
FLOAT CHAMBER	
PC	PP
FLOAT MOC	
FP	PP

3. VARIABLE TECHNICAL SPECIFICATIONS

Parameter	Options	Std
AIR VENT TYPE		Y
AS	½" Stop Plug	Y
AB	½" Ball Valve	Y
DRAIN TYPE		Y
DS	½" Stop Plug	Y
DB	½" Ball Valve	Y
INDICATOR TYPE		
CD	Capsule Desing Indicator (Toughend Glass Tube 25NB OD)	Y
FD	Flapper Desing Indicator	Y
RD	Roller Desing Indicator	Y
SCALE DETAILS		
SD1	LC 5 - Default	Y
SD2	LC 10	Y
Cust	Custom (Mention)	Y
SCALE UNIT DETAILS		
SU1	CM - Default	Y
SU3	Meter	Y
SU2	Percentage	Y
OTHER DETAILS		
Hydro Test	5 Kg/Cm2	
Branding	Flowtech	
Packing	Wooden / Other	