



FlowSM L270: Side Mounted Magnetic Level Indicator

FMIPL-SMMLI-F-S2-F1-FC1-xx-xx-xx-xx-NB-MM

1. PROCESS RANGE & LIMITATIONS			
Parameter		Specification	
Pressure Range		1 Bar to 8 Bar	
Temperature Range		10 Deg Celcius to 80 Deg Celcius	
2. FIXED TECHNICAL SPECIFICATIONS			
Parameter		Specification	
Tag No.			
C/C Height			
Casing	Aluminium Channel 2mm Thickness		
Scale	Aluminium with LC-5 / Direct Engraved on casing		
PROCESS CONNECTION TYPE			
F	Flange End		
PROCESS CONNECTION MOC			
S2	SS 316		
PROCESS CONNECTION STD			
F1	ASA 150 # RF		
FLOAT CHAMBER/PIPE			
FC1	SS 316 SCH 40		
3. VARIABLE TECHNICAL SPECIFICATIONS			
Parameter		Options	Std
FLOAT MOC			
FS1	SS 316 (Above Density 0.8 kg/cm2)		Y
FS3	Titanium (Below Density 0.8 kg/cm2)		Y
AIR VENT TYPE			
AS	½" Stop Plug		Y
AB	½" Ball Valve		Y
DRAIN TYPE			
DS	½" Stop Plug		Y
DB	½" Ball Valve		Y
INDICATOR TYPE			
CD	Capsule Desing Indicator (Toughend Glass Tube 25NB OD)		Y
FD	Flapper Desing Indicator		Y
RD	Roller Desing Indicator		Y
SCALE DETAILS			
SD1	LC 5 - Default		Y
SD2	LC 10		Y
Cust	Custom (Mention)		Y
SCALE UNIT DETAILS			
SU1	CM - Default		Y
SU3	Meter		Y
SU2	Percentage		Y
OTHER DETAILS			
Hydro Test	5 Kg/Cm2		
Branding	Flowtech		
Packing	Wooden / Other		