



FlowSM L270D: Side Mounted Magnetic Level Gauges			FMIPL-SMMLI-F-S2-F1-FC1-LR-W1-FLP-PS2-xx-xx-xx-xx-xx-xx-xx-NB-MM
1. PROCESS RANGE & LIMITATIONS			
Parameter		Specification	
Pressure Range		0 to 35 Bar	
Temperature Range		-20 Deg to 150 Deg Celcius	
2. FIXED TECHNICAL SPECIFICATIONS			
Parameter		Specification	
Tag No.			
C/C Height			
Casing		Aluminium Channel 2mm Thickness	
Scale		Aluminium with LC-5 / Direct Engraved on casing	
PROCESS CONNECTION TYPE			
F		Flange End	
PROCESS CONNECTION MOC			
S2		SS 316: Default	
PROCESS CONNECTION STD			
F1		ASA 150 # RF	
FLOAT CHAMBER			
FC1		SS 316 Schd. 10: Default	
WIRING TYPE			
W1		2 - Wire: Default for Level Transmitter	
ENCLOSURE PROTECTION			
FLP		Flameproof Aluminium Die Cast MOC	
POWER SUPPLY			
PS 2		24 VDC: Default for Level Transmitter	
3. VARIABLE TECHNICAL SPECIFICATIONS			
Parameter		Options	Std
FLOAT MOC			
FS1		SS 316 (Above Density 0.8)	Y
FS3		Titanium (Below Density 0.8)	Y
AIR VENT TYPE			
AS		½" Stop Plug	Y
AB		½" Ball Valve	Y
DRAIN TYPE			
DS		½" Stop Plug	Y
DB		½" Ball Valve	Y
INDICATOR TYPE			
CD		Capsule Desing Indicator (Toughend Glass Tube 25NB OD)	Y
FD		Flapper Desing Indicator	Y
RD		Roller Desing Indicator	Y
SCALE DETAILS			
SD1		LC 5	Y
SD2		LC 10	Y
Cust		Custom (Mention)	Y
SCALE UNIT DETAILS			
SU1		CM - Default	Y
SU3		Meter	Y
SU2		Percentage	Y
Transmitter/Switch Details			
LR		Transmitter Required (Max. 120 Deg. C.)	Y
L		L Type Switch: Default	N
HL		Hold On Type Switch	N
TRANSMITTER OUTPUT DETAILS		Not Applicable - If required only Switch	N
O1		4-20mA	N
O2		4-20mA + HART	N
OTHER DETAILS			
Fasteners MOC		SS 304	
Coating		Fine-Sand Blasting	
Hydro Test		10 Kg/Cm2	
Branding		Flowtech	
Packing		Wooden / Other	