



FlowSM L360: Side Mounted Magnetic Level Indicator

FMIPL-SMMLI-F-CU-F1-CU-xx-xx-xx-xx-xx-NB-MM

1. PROCESS RANGE & LIMITATIONS		
Parameter	Specification	
Pressure Range	1 Bar to 8 Bar	
Temperature Range	10 Deg Celcius to 80 Deg Celcius	
2. FIXED TECHNICAL SPECIFICATIONS		
Parameter	Specification	
Tag No.		
C/C Height		
Casing	Aluminium Channel 2mm Thickness	
Scale	Aluminium with LC-5 / Direct Engraved on casing	
PROCESS CONNECTION TYPE		
F	Flange End	
PROCESS CONNECTION MOC		
CU	SS 316L	
PROCESS CONNECTION STD		
F1	ASA 150 # RF	
FLOAT CHAMBER/PIPE		
3. VARIABLE TECHNICAL SPECIFICATIONS		
Parameter	Options	Std
FLOAT MOC		
FS1	SS 316L (Above Density 0.8)	Y
FS3	Titanium (Below Density 0.8)	Y
AIR VENT TYPE		
AS	½" Stop Plug	Y
AB	½" Ball Valve	Y
DRAIN TYPE		
DS	½" Stop Plug	Y
DB	½" Ball Valve	Y
INDICATOR TYPE		
CD	Capsule Desing Indicator (Toughend Glass Tube 25NB OD)	Y
FD	Flapper Desing Indicator	Y
RD	Roller Desing Indicator	Y
SCALE DETAILS		
SD1	LC 5 - Default	Y
SD2	LC 10	Y
Cust	Custom (Mention)	Y
SCALE UNIT DETAILS		
SU1	CM - Default	Y
SU3	Meter	Y
SU2	Percentage	Y
OTHER DETAILS		
Hydro Test	5 Kg/Cm2	
Branding	Flowtech	
Packing	Wooden / Other	