



FlowSM L360F: Side Mounted Magnetic Level Indicator			FM IPL - SMML I - CU - CU - XX - XX - XX - XX - XX - XX - XX - NB - MM
1. PROCESS RANGE & LIMITATIONS			
Parameter		Specification	
Pressure Range		1 Bar to 8 Bar	
Temperature Range		10 Deg Celcius to 80 Deg Celcius	
2. FIXED TECHNICAL SPECIFICATIONS			
Parameter		Specification	
Tag No.			
C/C Height			
Casing		Aluminium Channel 2mm Thickness	
Scale		Aluminium with LC-5 / Direct Engraved on casing	
PROCESS CONNECTION MOC			
CU		SS 316L	
FLOAT CHAMBER/PIPE			
3. VARIABLE TECHNICAL SPECIFICATIONS			
Parameter		Options	Std
FLOAT MOC			
FS2		SS 316L (Above Density 0.8)	Y
FS3		Titanium (Below Density 0.8)	Y
AIR VENT TYPE			
AS		½" Stop Plug	Y
AB		½" Ball Valve	Y
DRAIN TYPE			
DS		½" Stop Plug	Y
DB		½" Ball Valve	Y
INDICATOR TYPE			
CD		Capsule Desing Indicator (Toughend Glass Tube 25NB OD)	Y
FD		Flapper Desing Indicator	Y
RD		Roller Desing Indicator	Y
SCALE DETAILS			
SD1		LC 5 - Default	Y
SD2		LC 10	Y
Cust		Custom (Mention)	Y
SCALE UNIT DETAILS			
SU1		CM - Default	Y
SU3		Meter	Y
SU2		Percentage	Y
PROCESS CONNECTION TYPE			
F		Flange-End	Y
T		Threaded	Y
Cu		Custom Std: Mention Std	Y
PROCESS CONNECTION STD			
F2		ASA 300	Y
TB		BSP	Y
OTHER DETAILS			
Hydro Test		5 Kg/Cm2	
Branding		Flowtech	
Packing		Wooden / Other	