



FlowSM L360FD: Side Mounted Magnetic Level Gauges			FM IPL - SMML I - CU - CU - W1 - FLP - PS2 - XX - XX - XX - XX - XX - XX - XX - XX - NB - MM
1. PROCESS RANGE & LIMITATIONS			
Parameter		Specification	
Pressure Range		0 to 35 Bar	
Temperature Range		-20 Deg to 150 Deg Celcius	
2. FIXED TECHNICAL SPECIFICATIONS			
Parameter		Specification	
Tag No.			
C/C Height			
Casing	Aluminium Channel 2mm Thickness		
Scale	Aluminium with LC-5 / Direct Engraved on casing		
PROCESS CONNECTION MOC			
CU	SS 316L		
FLOAT CHAMBER			
WIRING TYPE			
W1	2 - Wire: Default for Level Transmitter		
ENCLOSURE PROTECTION			
FLP	Flameproof Aluminium Die Cast MOC		
POWER SUPPLY			
PS 2	24 VDC: Default for Level Transmitter		
3. VARIABLE TECHNICAL SPECIFICATIONS			
Parameter	Options	Std	
FLOAT MOC			
FS2	SS 316L (Above Density 0.8)	Y	
FS3	Titanium (Below Density 0.8)	Y	
AIR VENT TYPE			
AS	½" Stop Plug	Y	
AB	½" Ball Valve	Y	
DRAIN TYPE			
DS	½" Stop Plug	Y	
DB	½" Ball Valve	Y	
INDICATOR TYPE			
CD	Capsule Desing Indicator (Toughend Glass Tube 25NB OD)	Y	
FD	Flapper Desing Indicator	Y	
RD	Roller Desing Indicator	Y	
SCALE DETAILS			
SD1	LC 5	Y	
SD2	LC 10	Y	
Cust	Custom (Mention)	Y	
SCALE UNIT DETAILS			
SU1	CM - Default	Y	
SU3	Meter	Y	
SU2	Percentage	Y	
SWITCH DETAILS			
LR	Transmitter Required (Max. 120 Deg. C.)	Y	
L	L Type Switch: Default	N	
HL	Hold On Type Switch	N	
TRANSMITTER OUTPUT DETAILS			
O1	4-20mA	N	
O2	4-20mA + HART	N	
PROCESS CONNECTION TYPE			
F	Flange-End	Y	
T	Threaded	Y	
Cu	Custom Std: Mention Std	Y	
PROCESS CONNECTION STD			
F2	ASA 300	Y	
TB	BSP	Y	
OTHER DETAILS			
Fasteners MOC		SS 304	
Coating		Fine-Sand Blasting	
Hydro Test		10 Kg/Cm2	
Branding		Flowtech	
Packing		Wooden / Other	