

FlowSon L930

Compact and efficient level measurement of liquids and solids with In-built Display in Hazardous Area

Temperature Range -10 Deg Celcius to 90 Deg Celcius	Pressure Range 0.5 Bar to 4 Bar	Accuracy +/- 0.25% FSD
--	------------------------------------	---------------------------

1. Process Range & Limitations

Parameter	Specification
Measuring Principle	Radar (Guided Wave / Non-Contact)
Temperature Range	-10 Deg Celcius to 90 Deg Celcius
Pressure Range	0.5 Bar to 4 Bar
Accuracy	+/- 0.25% FSD
Sensor IP Grade	IP 68
Enclosure IP Grade	IP67

2. Fixed Technical Specifications

Parameter	Specification
Sensor MOC	ABS - Default
Display Mounting	
Output	4-20 mA + HART - Default
Power Supply	24 VDC - Default
Wiring Type	2 - Wire
Enclosure Protection	Weatherproof

3. Variable Technical Specifications

Code	Description
PROCESS CONNECTION TYPE	
PN2	Flange-End
PN1	Threaded - Default
CU	Custom (Mention)
SENSOR RANGE	
SR1	0-10 MTRS
SR2	0-15 MTRS
SR3	0-30 MTRS
ACCESSORIES	