



FlowSwirl L600: Vortex Flowmeter

For standard volumetric measurement of liquids & gases with Pressure & Temperature Compensation

FMIPL-VFM-IT1-PCT1-FT2-PC1-PCM2-PCS1-MT1-EPT1-02-CO1-WT2-PS1-NB

1. PROCESS RANGE & LIMITATIONS

Parameter	Specification
Pressure Range	-0.9 Bar to 30 Bar
Temperature Range	-25 Deg Celcius to 180 Deg Celcius

2. TECHNICAL SPECIFICATIONS

Parameter	Specification
Tag No.	
IBR TYPE	
IT1	Non-IBR Certified
P&T COMPENSATION TYPE	
PCT1	With Pressure & Temperature Compensation
FLOW TUBE MOC	
FT2	SS 316
PROCESS CONNECTION TYPE	
PC1	Flange-End
PROCESS CONNECTION MOC	
PCM2	SS 316
PROCESS CONNECTION STD.	
PCS1	ASA 150
MOUNTING TYPE	
MT1	Integral
ENCLOSURE PROTECTION TYPE	
EPT1	Weather-Proof : Aluminium Die Cast
OUTPUT	
O2	4-20mA + HART + Pulse
COMMUNICATION OUTPUT	
CO1	RS 485
WIRING TYPE	
WT2	3 Wire - With RS 485
POWER SUPPLY TYPE	
PS1	24 VDC
ACCESSORIES	
Controller	NA
Mating Flanges	NA
Accuracy	+/- 1% MV
OTHER DETAILS	
Branding	Flowtech
Packing	Others / Wooden