



FlowSwirl L600S: Vortex Flowmeter

For volumetric measurement of liquids & gases in Food & Beverage Industry with Temperature & Pressure Compensation

FM1PL-VFM-IT1-PCT2-FT2-PC3-PCM2-PCS1-MT1-EPT1-02-C01-WT2-PS1-NB

1. PROCESS RANGE & LIMITATIONS

Parameter	Specification
Pressure Range	-0.9 Bar to 30 Bar
Temperature Range	-25 Deg Celcius to 180 Deg Celcius

2. TECHNICAL SPECIFICATIONS

Parameter	Specification
Tag No.	
IBR TYPE	
IT1	Non-IBR Certified
P&T COMPENSATION TYPE	
PCT2	With Pressure & Temperature Compensation
FLOW TUBE MOC	
FT2	SS 316
PROCESS CONNECTION TYPE	
PC3	TC End Connection
PROCESS CONNECTION MOC	
PCM2	SS 316
PROCESS CONNECTION STD.	
PCS1	ASME Standard
MOUNTING TYPE	
MT1	Integral
ENCLOSURE PROTECTION TYPE	
EPT1	Weather-Proof : Aluminium Die Cast
OUTPUT	
O2	4-20mA + HART + Pulse
COMMUNICATION OUTPUT	
CO1	RS 485
WIRING TYPE	
WT2	3 Wire - With RS 485
POWER SUPPLY TYPE	
PS1	24 VDC
ACCESSORIES	
Controller	NA
Mating Flanges	NA
Accuracy	+/- 1% MV
OTHER DETAILS	
Branding	Flowtech
Packing	Others / Wooden