



FlowSwirl L600 F: Vortex Flowmeter

For high pressure volumetric measurement of liquids & gases with Temperature & Pressure Compensation

FMIPL-VFM-IT1-PCT2-FT2-PCM2-MT1-EPT1-02-C01-WT2-PS1-XX-XX-NB

1. PROCESS RANGE & LIMITATIONS

Parameter	Specification
Pressure Range	-0.9 Bar to 150 Bar
Temperature Range	-25 Deg Celcius to 180 Deg Celcius

2. FIXED TECHNICAL SPECIFICATIONS

Parameter	Specification
Tag No.	
IBR TYPE	
IT1	Non-IBR Certified
P&T COMPENSATION TYPE	
PCT2	With Pressure & Temperature Compensation
FLOW TUBE MOC	
FT2	SS 316
PROCESS CONNECTION MOC	
PCM2	SS 316
MOUNTING TYPE	
MT1	Integral
ENCLOSURE PROTECTION TYPE	
EPT1	Weather-Proof : Aluminium Die Cast
OUTPUT	
O2	4-20mA + HART + Pulse
COMMUNICATION OUTPUT	
CO1	RS 485
WIRING TYPE	
WT2	3 Wire - With RS 485
POWER SUPPLY TYPE	
PS1	24 VDC

3. VARIABLE TECHNICAL SPECIFICATIONS

Parameter	Options	Std
PROCESS CONNECTION TYPE		
PC1	Flange-End	Y
PC2	Wafer Connection	Y
PC4	Threaded	Y
PROCESS CONNECTION STD		
PCS1	ASA 150	Y
PCS2	ASA 300	Y
Cu	Custom Std: Mention Std	Y
ACCESSORIES		
Controller	NA	N
Mating Flanges	NA	Y
Accuracy	+/- 1% MV	N

OTHER DETAILS

Branding	Flowtech
Packing	Others / Wooden