

FlowTLI L180F: Tubular Level Indicator			FM1PL-TLI-WP4-P-CC-CP-DR-GP-FS-W-XX-XX-NB-MM
1. PROCESS RANGE & LIMITATIONS			
Parameter		Specification	
2. FIXED TECHNICAL SPECIFICATIONS			
Parameter		Specification	
Tag No.			
C-C Height			
Casing	3mm Thickness in PVC and FRP		
Glass Details	Borosilicate of 19 mm OD		
Scale Details	Least Count of 5mm		
Valve	Not Required		
Valve Type	Horizontal Inbuilt Isolation Needle Valve		
WETTED PARTS MOC			
WP4	PP		
PROCESS CONNECTION MOC			
P	PP		
CAGING TYPE			
CC	C - Channel		
CAGE MOC			
CP	PVC		
SCALE MOC			
DR	Direct Engraved on Channel		
GLAND MOC			
GP	PVC		
FLAT TYPE			
FS	Single		
FLANGE TYPE			
W	Welded		
Protection	Not Applicable/ Acrylic Guard		
3. VARIABLE TECHNICAL SPECIFICATIONS			
Parameter		Options	Std
PROCESS CONNECTION TYPE			
F	Flange end		Y
T	Threaded		Y
PROCESS CONNECTION STD			
F1	ASA 150 # RF		Y
F2	ASA 300 #RF		Y
TB1	BSP (M)		Y
TB2	BSP (F)		Y
TN1	NPT (M)		Y
TN2	NPT (F)		Y
ACCESSORIES			
Air Vent	3/4" BSP Stop Plug/ 1/2" BSP Ball Valve		Y
Drain	3/4" BSP Stop Plug/ 1/2" BSP Ball Valve		Y
OTHER DETAILS			
Hydro Test	3 kg/cm2		
Fasteners	GI Plated		