



FlowTLI L180FV: Tubular Level Indicator

FM IPL - TLI - WP4 - P - CC - CP - DR - GP - FS - W - VP - XX - XX - NB - MM

1. PROCESS RANGE & LIMITATIONS

Parameter	Specification
-----------	---------------

2. FIXED TECHNICAL SPECIFICATIONS

Parameter	Specification
Tag No.	
C-C Height	
Casing	3mm Thickness in PVC and FRP
Glass Details	Borosilicate of 19 mm OD
Scale Details	Least Count of 5mm
Valve	Required
Valve Type	Horizontal Inbuilt Isolation Needle Valve
WETTED PARTS MOC	
WP4	PP
PROCESS CONNECTION MOC	
P	PP
CAGING TYPE	
CC	C - Channel
CAGE MOC	
CP	PVC
SCALE MOC	
DR	Direct Engraved on Channel
GLAND MOC	
GP	PVC
FLAT TYPE	
FS	Single
FLANGE TYPE	
W	Welded
Valve Body MOC	
VP	PP
Protection	Not Applicable/ Acrylic Guard

3. VARIABLE TECHNICAL SPECIFICATIONS

Parameter	Options	Std
PROCESS CONNECTION TYPE		
F	Flange end	Y
T	Threaded	Y
PROCESS CONNECTION STD		
F1	ASA 150 # RF	Y
F2	ASA 300 #RF	Y
TB1	BSP (M)	Y
TB2	BSP (F)	Y
TN1	NPT (M)	Y
TN2	NPT (F)	Y
ACCESSORIES		
Air Vent	3/4" BSP Stop Plug/ 1/2" BSP Ball Valve	Y
Drain	3/4" BSP Stop Plug/ 1/2" BSP Ball Valve	Y

OTHER DETAILS

Hydro Test	3 kg/cm2
Fasteners	GI Plated