

FLOWTECH Flowtech Measuring Instruments Pvt. Ltd. ISO 9001:2015 Certified	
FlowTLI L180V: Tubular Level Indicator	
FMIPL-TLI-WP4-F-P-F1-CC-CP-DR-GP-FS-W-VP-NB-MM	
1. PROCESS RANGE & LIMITATIONS	
Parameter	Specification
2. TECHNICAL SPECIFICATIONS	
Parameter	Specification
Tag No.	
C-C Height	
Casing	3mm Thickness in PVC and FRP
Glass Details	Borosilicate of 19 mm OD
Scale Details	Least Count of 5mm
Valve	Required
Valve Type	Horizontal Inbuilt Isolation Needle Valve
WETTED PARTS MOC	
WP4	PP
PROCESS CONNECTION TYPE	
F	Flange end
PROCESS CONNECTION MOC	
P	PP
PROCESS CONNECTION STD	
F1	ASA 150 # RF
CAGING TYPE	
CC	C - Channel
CAGE MOC	
CP	PVC
SCALE MOC	
DR	Direct Engraved on Channel
GLAND MOC	
GP	PVC
FLAT TYPE	
FS	Single
FLANGE TYPE	
W	Welded
Valve Body MOC	
VP	PP
ACCESSORIES	
Protection	Not Applicable/ Acrylic Guard
Air Vent	3/4" BSP Stop Plug/ 1/2" BSP Ball Valve
Drain	3/4" BSP Stop Plug/ 1/2" BSP Ball Valve
OTHER DETAILS	
Hydro Test	3 kg/cm2
Fasteners	GI Plated