



FlowTLI L270F: Tubular Level Indicator

FMIPL-TLI-CC-CM-SA1-GM-FS-SO-xx-xx-xx-xx-NB-MM

1. PROCESS RANGE & LIMITATIONS

Parameter	Specification
-----------	---------------

2. FIXED TECHNICAL SPECIFICATIONS

Parameter	Specification
Tag No.	
C-C Height	
Casing	1.5mm Thickness in MS
Glass Details	Borosilicate of 19 mm OD
Scale Details	Least Count of 5mm
Valve	Not Required
Valve Type	Horizontal Inbuilt Isolation Needle Valve
CAGING TYPE	
CC	C - Channel
CAGE MOC	
CM	MS
SCALE MOC	
SA1	Acrylic
GLAND MOC	
GM	MS
FLAT TYPE	
FS	Single
FLANGE TYPE	
SO	Slip-on
Protection	Not Applicable / Acrylic Guard

3. VARIABLE TECHNICAL SPECIFICATIONS

Parameter	Options	Std
WETTED PARTS MOC		
WP	MS	Y
WP1	SS 304	Y
WP2	SS 316	Y
WP3	SS 316L	Y
PROCESS CONNECTION TYPE		
F	Flange end	Y
T	Threaded	Y
T1	TC Joint	Y
CU	Cust.	Y
PROCESS CONNECTION MOC		
C	MS	Y
S1	SS 304	Y
S2	SS 316	Y
S3	SS 316L	Y
PROCESS CONNECTION STD		
F1	ASA 150 # RF	Y
F2	ASA 300#RF	Y
TB1	BSP(M)	Y
TB2	BSP (F)	Y
TN1	NPT(M)	Y
TN2	NPT (F)	Y
TC	TC Joint	Y
ACCESSORIES		
Air Vent	3/4" BSP Stop Plug/ 1/2" BSP Ball Valve	Y
Drain	3/4" BSP Stop Plug/ 1/2" BSP Ball Valve	Y
OTHER DETAILS		
Hydro Test	3 kg/cm2	
Fasteners	GI Plated	