

FlowTLI L270FV: Tubular Level Indicator			FMIPL-TLI-CC-CM-SA1-GM-FS-S0-xx-xx-xx-xx-NB-MM
1. PROCESS RANGE & LIMITATIONS			
Parameter		Specification	
2. FIXED TECHNICAL SPECIFICATIONS			
Parameter		Specification	
Tag No.			
C-C Height			
Casing	1.5mm Thickness in MS		
Glass Details	Borosilicate of 19 mm OD		
Scale Details	Least Count of 5mm		
Valve	Required		
Valve Type	Horizontal Inbuilt Isolation Needle Valve		
CAGING TYPE			
CC	C - Channel		
CAGE MOC			
CM	MS		
SCALE MOC			
SA1	Acrylic		
GLAND MOC			
GM	MS		
FLAT TYPE			
FS	Single		
FLANGE TYPE			
SO	Slip-on		
Protection	Not Applicable / Acrylic Guard		
3. VARIABLE TECHNICAL SPECIFICATIONS			
Parameter		Options	Std
WETTED PARTS MOC			
W	MS		Y
WP1	SS 304		Y
WP2	SS 316		Y
WP3	SS 316L		Y
PROCESS CONNECTION TYPE			
F	Flange end		Y
T	Threaded		Y
T1	TC Joint		Y
CU	Cust.		Y
PROCESS CONNECTION MOC			
C	MS		Y
S1	SS 304		Y
S2	SS 316		Y
S3	SS 316L		Y
PROCESS CONNECTION STD			
F1	ASA 150 # RF		Y
F2	ASA 300#RF		Y
TB1	BSP(M)		Y
TB2	BSP (F)		Y
TN1	NPT(M)		Y
TN2	NPT (F)		Y
TC	TC Joint		Y
Vlave Body MOC			
VM	MS		Y
VS1	SS 304		Y
VS2	SS 316L		Y
VS3	SS 316L		Y
ACCESSORIES			
Air Vent	3/4" BSP Stop Plug/ 1/2" BSP Ball Valve		Y
Drain	3/4" BSP Stop Plug/ 1/2" BSP Ball Valve		Y
OTHER DETAILS			
Hydro Test	3 kg/cm2		
Fasteners	GI Plated		