



FlowTLI L270V: Tubular Level Indicator

FM IPL - TLI - WP - F - C - F1 - CC - CM - SA1 - GM - FS - SO - VM - NB - MM

1. PROCESS RANGE & LIMITATIONS

Parameter	Specification
-----------	---------------

2. TECHNICAL SPECIFICATIONS

Parameter	Specification
Tag No.	
C-C Height	
Casing	1.5mm Thickness in MS
Glass Details	Borosilicate of 19 mm OD
Scale Details	Least Count of 5mm
Valve	Required
Valve Type	Horizontal Inbuilt Isolation Needle Valve
WETTED PARTS MOC	
WP	MS
PROCESS CONNECTION TYPE	
F	Flange end
PROCESS CONNECTION MOC	
C	MS
PROCESS CONNECTION STD	
F1	ASA 150 # RF
CAGING TYPE	
CC	C - Channel
CAGE MOC	
CM	MS
SCALE MOC	
SA1	Acrylic
GLAND MOC	
GM	MS
FLAT TYPE	
FS	Single
FLANGE TYPE	
SO	Slip-on
Valve Body MOC	
VM	MS
Protection	Not Applicable/ Acrylic Gurd
ACCESSORIES	
Air Vent	3/4" BSP Stop Plug/ 1/2" BSP Ball Valve
Drain	3/4" BSP Stop Plug/ 1/2" BSP Ball Valve
OTHER DETAILS	
Hydro Test	3 kg/cm2
Fasteners	GI Plated