

FLOWTECH Flowtech Measuring Instruments Pvt. Ltd. ISO 9001:2015 Certified	
FlowTLI L360: Tubular Level Indicator FMIPL-TLI-WP1-F-S1-F1-CC-CS1-DR-GS-FS-SO-NB-MM	
1. PROCESS RANGE & LIMITATIONS	
Parameter	Specification
2. TECHNICAL SPECIFICATIONS	
Parameter	Specification
Tag No.	
C-C Height	
Casing	1.5mm Thickness in SS
Glass Details	Borosilicate of 19 mm OD
Scale Details	Least Count of 5mm
Valve	Not Required
Valve Type	Horizontal Inbuilt Isolation Needle Valve
WETTED PARTS MOC	
WP1	SS 304
PROCESS CONNECTION TYPE	
F	Flange end
PROCESS CONNECTION MOC	
S1	SS 304
PROCESS CONNECTION STD	
F1	ASA 150 # RF
CAGING TYPE	
CC	C - Channel
CAGE MOC	
CS1	SS 304
SCALE MOC	
DR	Direct Engraved on Casing
GLAND MOC	
GS	SS 304
FLAT TYPE	
FS	Single
FLANGE TYPE	
SO	Slip-on
Protection	Not Applicable / Acrylic Guard
ACCESSORIES	
Air Vent	3/4" BSP Stop Plug/ 1/2" BSP Ball Valve
Drain	3/4" BSP Stop Plug/ 1/2" BSP Ball Valve
OTHER DETAILS	
Hydro Test	3 kg/cm2
Fasteners	SS 304

Technical Datasheet Rev.01

Page 1/1

Flowtech Measuring Instruments Pvt. Ltd.