



FlowTLI L360V: Tubular Level Indicator

FM1PL-TLI-WP1-F-S1-F1-CC-CS1-DR-GS-FS-S0-VS1-NB-MM

1. PROCESS RANGE & LIMITATIONS

| Parameter | Specification |
|-----------|---------------|
|-----------|---------------|

2. TECHNICAL SPECIFICATIONS

|                         |                                           |
|-------------------------|-------------------------------------------|
| Parameter               | Specification                             |
| Tag No.                 |                                           |
| C-C Height              |                                           |
| Casing                  | 1.5mm Thickness in SS                     |
| Glass Details           | Borosilicate of 19 mm OD                  |
| Scale Details           | Least Count of 5mm                        |
| Valve                   | Required                                  |
| Valve Type              | Horizontal Inbuilt Isolation Needle Valve |
| WETTED PARTS MOC        |                                           |
| WP1                     | SS 304                                    |
| PROCESS CONNECTION TYPE |                                           |
| F                       | Flange end                                |
| PROCESS CONNECTION MOC  |                                           |
| S1                      | SS 304                                    |
| PROCESS CONNECTION STD  |                                           |
| F1                      | ASA 150 # RF                              |
| CAGING TYPE             |                                           |
| CC                      | C - Channel                               |
| CAGE MOC                |                                           |
| CS1                     | SS 304                                    |
| SCALE MOC               |                                           |
| DR                      | Direct Engraved on Casing                 |
| GLAND MOC               |                                           |
| GS                      | SS 304                                    |
| FLAT TYPE               |                                           |
| FS                      | Single                                    |
| FLANGE TYPE             |                                           |
| SO                      | Slip-on                                   |
| Valve Body MOC          |                                           |
| VS1                     | SS 304                                    |
| Protection              | Not Applicable / Acrylic Guard            |
| ACCESSORIES             |                                           |
| Air Vent                | 3/4" BSP Stop Plug/ 1/2" BSP Ball Valve   |
| Drain                   | 3/4" BSP Stop Plug/ 1/2" BSP Ball Valve   |
| OTHER DETAILS           |                                           |
| Hydro Test              | 3 kg/cm2                                  |
| Fasteners               | SS 304                                    |