



FlowTLI L450: Tubular Level Indicator

FMIPL-TLI-WP2-F-S2-F1-CC-CS2-DR-GS1-FS-S0-NB-MM

1. PROCESS RANGE & LIMITATIONS

Parameter	Specification
-----------	---------------

2. TECHNICAL SPECIFICATIONS

Parameter	Specification
-----------	---------------

Tag No.	
---------	--

C-C Height	
------------	--

Casing	1.5mm Thickness in SS
--------	-----------------------

Glass Details	Borosilicate of 19 mm OD
---------------	--------------------------

Scale Details	Least Count of 5mm
---------------	--------------------

Valve	Not Required
-------	--------------

Valve Type	Horizontal Inbuilt Isolation Needle Valve
------------	---

WETTED PARTS MOC	
------------------	--

WP2	SS 316
-----	--------

PROCESS CONNECTION TYPE	
-------------------------	--

F	Flange end
---	------------

PROCESS CONNECTION MOC	
------------------------	--

S2	SS 316
----	--------

PROCESS CONNECTION STD	
------------------------	--

F1	ASA 150 # RF
----	--------------

CAGING TYPE	
-------------	--

CC	C - Channel
----	-------------

CAGE MOC	
----------	--

CS2	SS 316
-----	--------

SCALE MOC	
-----------	--

DR	Direct Engraved on Casing
----	---------------------------

GLAND MOC	
-----------	--

GS1	SS 316
-----	--------

FLAT TYPE	
-----------	--

FS	Single
----	--------

FLANGE TYPE	
-------------	--

SO	Slip-on
----	---------

Protection	Not Applicable / Acrylic Guard
------------	--------------------------------

ACCESSORIES	
-------------	--

Air Vent	3/4" BSP Stop Plug/ 1/2" BSP Ball Valve
----------	---

Drain	3/4" BSP Stop Plug/ 1/2" BSP Ball Valve
-------	---

OTHER DETAILS	
---------------	--

Hydro Test	3 kg/cm2
------------	----------

Fasteners	SS 304
-----------	--------