



FlowTLI L450FV: Tubular Level Indicator

FM IPL - TLI - CC - CS2 - DR - GS1 - FS - S0 - XX - XX - XX - XX - NB - MM

1. PROCESS RANGE & LIMITATIONS

Parameter	Specification
-----------	---------------

2. FIXED TECHNICAL SPECIFICATIONS

Parameter	Specification
Tag No.	
C-C Height	
Casing	1.5mm Thickness in SS
Glass Details	Borosilicate of 19 mm OD
Scale Details	Least Count of 5mm
Valve	Required
Valve Type	Horizontal Inbuilt Isolation Needle Valve
CAGING TYPE	
CC	C - Channel
CAGE MOC	
CS2	SS 316
SCALE MOC	
DR	Direct Engraved on Casing
GLAND MOC	
GS1	SS 316
FLAT TYPE	
FS	Single
FLANGE TYPE	
SO	Slip-on
Protection	Not Applicable / Acrylic Guard

3. VARIABLE TECHNICAL SPECIFICATIONS

Parameter	Options	Std
WETTED PARTS MOC		
WP2	SS 316	Y
WP3	SS 316L	Y
PROCESS CONNECTION TYPE		
F	Flange end	Y
T	Threaded	Y
T1	TC Joint	Y
CU	Cust.	Y
PROCESS CONNECTION MOC		
S2	SS 316	Y
S3	SS 316L	Y
PROCESS CONNECTION STD		
F1	ASA 150 # RF	Y
F2	ASA 300 #RF	Y
TB1	BSP (M)	Y
TB2	BSP (F)	Y
TN1	NPT (M)	Y
TN2	NPT (F)	Y
TC	TC Joint	Y
Valve Body MOC		
VS2	SS 316	Y
VS3	SS 316L	Y
ACCESSORIES		
Air Vent	3/4" BSP Stop Plug/ 1/2" BSP Ball Valve	Y
Drain	3/4" BSP Stop Plug/ 1/2" BSP Ball Valve	Y

OTHER DETAILS

Hydro Test	3 kg/cm2
Fasteners	SS 304