



FlowTLI L450V: Tubular Level Indicator

FMIPL-TLI-WP2-F-S2-F1-CC-CS2-DR-GS1-FS-S0-VS2-NB-MM

1. PROCESS RANGE & LIMITATIONS

Parameter	Specification
-----------	---------------

2. TECHNICAL SPECIFICATIONS

Parameter	Specification
Tag No.	
C-C Height	
Casing	1.5mm Thickness in SS
Glass Details	Borosilicate of 19 mm OD
Scale Details	Least Count of 5mm
Valve	Required
Valve Type	Horizontal Inbuilt Isolation Needle Valve
WETTED PARTS MOC	
WP2	SS 316
PROCESS CONNECTION TYPE	
F	Flange end
PROCESS CONNECTION MOC	
S2	SS 316
PROCESS CONNECTION STD	
F1	ASA 150 # RF
CAGING TYPE	
CC	C - Channel
CAGE MOC	
CS2	SS 316
SCALE MOC	
DR	Direct Engraved on Casing
GLAND MOC	
GS1	SS 316
FLAT TYPE	
FS	Single
FLANGE TYPE	
SO	Slip-on
Valve Body MOC	
VS2	SS 316
Protection	Not Applicable / Acrylic Guard
ACCESSORIES	
Air Vent	3/4" BSP Stop Plug/ 1/2" BSP Ball Valve
Drain	3/4" BSP Stop Plug/ 1/2" BSP Ball Valve
OTHER DETAILS	
Hydro Test	3 kg/cm2
Fasteners	SS 304