



FlowTurb L270B

In-built Battery Operated Measurement of simple liquids with Low or No Conductivity

FM1PL-TFM-FT2-F-S2-F1IR-W2-WP-M-CR-XX-XX-NB

1. PROCESS RANGE & LIMITATIONS

Parameter	Specification
Pressure Range	-0.9 Bar to 25 Bar
Temperature Range	- 20 Deg to 150 Deg Celcius
Viscosity Range	0 to 10 Cp

2. FIXED TECHNICAL SPECIFICATIONS

Parameter	Specification
Tag No.	
FLOW TUBE MOC	
FT 2	SS 316
PROCESS CONNECTION TYPE	
F	Flange End
PROCESS CONNECTION MOC	
S2	SS 316
PROCESS CONNECTION STD	
F1	ASA 150 # RF
IMPELLER TYPE	
IR	Regular (Default MOC SS 410)
PROTECTION TYPE (IP 67 Protection)	
WP	Weatherproof
OUTPUT	Note: 24 VDC external power supply is needed for Output
M	4-20mA + Pulse + 2 Relay
COMMUNICATION	
CR	Note: 24 VDC external power supply is needed for Communication Output
POWER SUPPLY	RS 485
MOUNTING	
I	With 3.6 V Lithium Battery: 1 Cell AA Size
	Integral Type

3. VARIABLE TECHNICAL SPECIFICATIONS

Parameter	Options	Std
-----------	---------	-----

OTHER DETAILS

ACCESSORIES	
GN	Gasket & Nut Bolts
WI	Extra Wire
NA	Not Applicable
Accuracy	+/- 1% MV
Branding	Flowtech
Packing	Wooden / Other