

FlowTurb L270 Ex

Measurement of Hazardous liquids with Low or No Conductivity

FMIPL-TFM-FT2-F-S2-F1-IR-W2-FLP-M-CR-XX-XX-NB

1. PROCESS RANGE & LIMITATIONS

| Parameter         | Specification               |
|-------------------|-----------------------------|
| Pressure Range    | -0.9 Bar to 25 Bar          |
| Temperature Range | - 20 Deg to 150 Deg Celcius |
| Viscosity Range   | Max. 5 Cp                   |

2. FIXED TECHNICAL SPECIFICATIONS

|                                    |                                           |
|------------------------------------|-------------------------------------------|
| Parameter                          | Specification                             |
| Tag No.                            |                                           |
| FLOW TUBE MOC                      |                                           |
| FT 2                               | SS 316                                    |
| PROCESS CONNECTION TYPE            |                                           |
| F                                  | Flange End                                |
| PROCESS CONNECTION MOC             |                                           |
| S2                                 | SS 316                                    |
| PROCESS CONNECTION STD             |                                           |
| F1                                 | ASA 150 # RF                              |
| IMPELLER TYPE                      |                                           |
| IR                                 | Regular (Default MOC SS 410)              |
| WIRE TYPE                          |                                           |
| W2                                 | 4-Wire                                    |
| PROTECTION TYPE (IP 67 Protection) |                                           |
| FLP                                | Flameproof - PESO Certified - IIA IIB IIC |
| OUTPUT                             |                                           |
| M                                  | 4-20mA + Pulse + 2 Relay                  |
| COMMUNICATION                      |                                           |
| CR                                 | RS 485                                    |

3. VARIABLE TECHNICAL SPECIFICATIONS

|              |                         |     |
|--------------|-------------------------|-----|
| Parameter    | Options                 | Std |
| MOUNTING     |                         |     |
| I            | Integral Type           | Y   |
| RE           | Remote Type - XX Meters | Y   |
| POWER SUPPLY |                         |     |
| AC           | 230 V AC                | Y   |
| DC           | 24 V DC - Default       | Y   |

OTHER DETAILS

|              |                                               |
|--------------|-----------------------------------------------|
| RELAY OUTPUT | 2 Relay Outputs - 5 Amp - Only in Remote Type |
| ACCESSORIES  |                                               |
| GN           | Gasket & Nut Bolts                            |
| WI           | Extra Wire                                    |
| NA           | Not Applicable                                |
| Accuracy     | +/- 1% MV                                     |
| Branding     | Flowtech                                      |
| Packing      | Wooden / Other                                |