

FLOWTECH Flowtech Measuring Instruments Pvt. Ltd. ISO 9001:2015 Certified		
FlowTurb L270 Measurement of simple liquids with Low or No Conductivity		FMIPL-TFM-FT2-F-S2-F1IR-W2-WP-M-CR-xx-xx-NB
1. PROCESS RANGE & LIMITATIONS		
Parameter	Specification	
Pressure Range	-0.9 Bar to 25 Bar	
Temperature Range	- 20 Deg to 150 Deg Celcius	
Viscosity Range	0 to 10 Cp	
2. FIXED TECHNICAL SPECIFICATIONS		
Parameter	Specification	
Tag No.		
FLOW TUBE MOC		
FT 2	SS 316	
PROCESS CONNECTION TYPE		
F	Flange End	
PROCESS CONNECTION MOC		
S2	SS 316	
PROCESS CONNECTION STD		
F1	ASA 150 # RF	
IMPELLER TYPE		
IR	Regular (Default MOC SS 410)	
WIRE TYPE		
W2	4-Wire	
PROTECTION TYPE (IP 67 Protection)		
WP	Weatherproof	
OUTPUT		
M	4-20mA + Pulse + 2 Relay	
COMMUNICATION		
CR	RS 485	
POWER SUPPLY	Both 230 VAC & 24VDC (If mounting is Integral, then Power Supply shall be 24VDC Only)	
3. VARIABLE TECHNICAL SPECIFICATIONS		
Parameter	Options	Std
MOUNTING		
I	Integral Type	Y
RE	Remote Type - XX Meters	Y
OTHER DETAILS		
ACCESSORIES		
RELAY OUTPUT	2 Relay Outputs - 5 Amp - Only in Remote Type	
GN	Gasket & Nut Bolts	
WI	Extra Wire	
NA	Not Applicable	
Accuracy	+/- 1% MV	
Branding	Flowtech	
Packing	Wooden / Other	