

Flowtech Measuring Instruments Pvt. Ltd.

ISO 9001:2015 Certified

FlowTurb L270 ExF

Measurement of Hazardous liquids with Low or No Conductivity

FMIPL - TFM - FT2 - S2 - IR - W2 - FLP - M - CR - xx - xx - xx - NB

1. PROCESS RANGE & LIMITATIONS

Parameter	Specification
Pressure Range	-0.9 Bar to 25 Bar
Temperature Range	- 20 Deg to 150 Deg Celcius
Viscosity Range	Max. 5 Cp

2. FIXED TECHNICAL SPECIFICATIONS

Parameter	Specification
Tag No.	
FLOW TUBE MOC	
FT 2	SS 316
PROCESS CONNECTION MOC	
S2	SS 316
IMPELLER TYPE	
IR	Regular (Default MOC SS 410)
WIRE TYPE	
W2	4-Wire
PROTECTION TYPE (IP 67 Protection)	
FLP	Flameproof - PESO Certified - IIA IIB IIC
OUTPUT	
M	4-20mA + Pulse + 2 Relay
COMMUNICATION	
CR	RS 485
POWER SUPPLY	Both 230VAC & 24VDC

3. VARIABLE TECHNICAL SPECIFICATIONS

Parameter	Options	Std
PROCESS CONNECTION TYPE		
F	Flange-End: Default	Y
T	Threaded	Y
Cu	Custom Std: Mention Std	Y
PROCESS CONNECTION STD		
F1	ASA 150 Class	Y
MOUNTING		
I	Integral Type	Y
RE	Remote Type - XX Meters	Y
OTHER DETAILS		
RELAY OUTPUT	2 Relay Outputs - 5 Amp - Only in Remote Type	
ACCESSORIES		
GN	Gasket & Nut Bolts	
WI	Extra Wire	
NA	Not Applicable	
Accuracy	+/- 1% MV	
Branding	Flowtech	
Packing	Wooden / Other	

Technical Datasheet Rev.01

Page 1/1

Flowtech Measuring Instruments Pvt. L