



FlowTurb L630

Measurement of simple liquids with Low or No Conductivity for Food Grade Applications

FMIPL-TFM-FT2-T1-S2-CU-IR-W2-WP-M-CR-XX-XX-XX-NB

1. PROCESS RANGE & LIMITATIONS

Parameter	Specification
Pressure Range	-0.9 Bar to 25 Bar
Temperature Range	- 20 Deg to 150 Deg Celcius
Viscosity Range	Max. 5 Cp

2. FIXED TECHNICAL SPECIFICATIONS

Parameter	Specification
Tag No.	
FLOW TUBE MOC	
FT 2	SS 316
PROCESS CONNECTION TYPE	
T1	TC Connection
PROCESS CONNECTION MOC	
S2	SS 316
PROCESS CONNECTION STD	
Cu	ASME
IMPELLER TYPE	
IR	Regular (Default MOC SS 410)
WIRE TYPE	
W2	4-Wire
PROTECTION TYPE (IP 67 Protection)	
WP	Weatherproof
OUTPUT	
M	4-20mA + Pulse + 2 Relay
COMMUNICATION	
CR	RS 485

3. VARIABLE TECHNICAL SPECIFICATIONS

Parameter	Options	Std
MOUNTING		
I	Integral Type	Y
RE	Remote Type - XX Meters	Y
POWER SUPPLY	If Mounting is Integral, then Power Supply is 24VDC Only	Y
AC	230 V AC	Y
DC	24 V DC - Default	Y
RELAY OUTPUT		
RO1	Not Applicable. (Applicable only in remote type Controllers)	Y
RO2	2 Relay Outputs - 5 Amp	Y

OTHER DETAILS

ACCESSORIES	
GN	Gasket & Nut Bolts
WI	Extra Wire
NA	Not Applicable
Accuracy	+/- 1% MV
Branding	Flowtech
Packing	Wooden / Other