



FlowTurb L900 F

Measurement of Hazardous liquids with Low or No Conductivity

FMIPL-TFM-FT2-S2-IR-W2-M-XX-XX-NB

1. PROCESS RANGE & LIMITATIONS

Parameter	Specification
Pressure Range	-0.9 Bar to 25 Bar
Temperature Range	- 20 Deg to 150 Deg Celcius
Viscosity Range	Max. 5 Cp

2. FIXED TECHNICAL SPECIFICATIONS

Parameter	Specification
Tag No.	
FLOW TUBE MOC	
FT 2	SS 316
PROCESS CONNECTION MOC	
S2	SS 316
IMPELLER TYPE	
IR	Regular (Default MOC SS 410)
WIRE TYPE	
W2	2-Wire
MOUNTING	
WO	Pickup Sensor With Output - No Display
OUTPUT	
M	4-20mA + Pulse + 2 Relay
POWER SUPPLY	8-28 VDC

3. VARIABLE TECHNICAL SPECIFICATIONS

Parameter	Options	Std
PROCESS CONNECTION TYPE		
F	Flange-End: Default	Y
T	Threaded	Y
Cu	Custom Std: Mention Std	Y
PROCESS CONNECTION STD		
F1	ASA 150 Class	Y

OTHER DETAILS

RELAY OUTPUT	2 Relay Outputs - 5 Amp - Only in Remote Type
ACCESSORIES	
GN	Gasket & Nut Bolts
WI	Extra Wire
NA	Not Applicable
Accuracy	+/- 1% MV
Branding	Flowtech
Packing	Wooden / Other