

FLOWTECH

Flowtech Measuring Instruments Pvt. Ltd.

ISO 9001:2015 Certified

FlowVal L450

Measurement of Highly Corrosive & Viscose Liquids

FMIPL-DOGFM-

1. PROCESS RANGE & LIMITATIONS

Parameter	Specification
Pressure Range	-0.9 Bar to 30 Bar
Temperature Range	-10 Deg Celcius to 100 Deg Celcius
Viscosity Range	10 Cp to 300 Cp

2. FIXED TECHNICAL SPECIFICATIONS

Parameter	Specification
Tag No.	
Accuracy	+/- 0.5 to 1% of MV

3. VARIABLE TECHNICAL SPECIFICATIONS

Parameter	Options	Std
MOUNTING TYPE		
MT1	Integral Mounting	Y
MT2	Remote Mounting - MTRs	Y
Screen	LCD With Backlight	Y
Readings	Flow Rate & Flow Totalizer	Y
Branding	Flowtech	Y
Packing	Wooden / Other	Y

OTHER DETAILS

PROCESS CONNECTION TYPE	
PC2	Threaded
PROCESS CONNECTION MOC	
PCM4	SS 316
PROCESS CONNECTION STD.	
PCS2	1/4" BSP (F)
ROTOR MOC	
RM1	SS 316
SHAFT MOC	
SM1	SS 316
DISPLAY DETAILS	
DD2	Weather-Proof
OUTPUT	
O1	4-20mA
COMMUNICATION OUTPUT	
CO1	RS 485
POWER SUPPLY	Both 230VAC & 24VDC

Technical Datasheet Rev.01

Page 1/1

Flowtech Measuring Instruments Pvt. Ltd.