



FlowVal L450F

Standard Measurement of High Viscose Liquids with Customised Process Connection

FMIPL-D06FM-

1. PROCESS RANGE & LIMITATIONS

Parameter	Specification
Pressure Range	-0.9 Bar to 300 Bar
Temperature Range	-10 Deg Celcius to 100 Deg Celcius
Viscosity Range	10 Cp to 300 Cp

2. FIXED TECHNICAL SPECIFICATIONS

Parameter	Specification
Tag No.	
Accuracy	+/- 0.5 to 1% of MV

3. VARIABLE TECHNICAL SPECIFICATIONS

Parameter	Options	Std
PROCESS CONNECTION TYPE		
PC1	Flange-End	Y
PC3	TC- Connection	Y
Cu	Customised Standard - Mention Standard	Y
PROCESS CONNECTION STD.		
PCS1	ASA 150 Class	Y
MOUNTING TYPE		
MT1	Integral Mounting	Y
MT2	Remote Mounting - MTRs	Y
Screen	LCD With Backlight	Y
Readings	Flow Rate & Flow Totalizer	Y
Branding	Flowtech	Y
Packing	Wooden / Other	Y

OTHER DETAILS

PROCESS CONNECTION MOC	
PCM3	SS 316
ROTOR MOC	
RM2	SS 316
SHAFT MOC	
SM1	SS 316
DISPLAY DETAILS	
DD2	Weather-Proof
OUTPUT	
O1	4-20mA
POWER SUPPLY	Both 230VAC & 24VDC
COMMUNICATION OUTPUT	
CO1	RS 485