

SO / PO Reference SO-2026-0542	QTN Reference QTN-2026-0891	Client Reliance Industries Ltd.	Project Jamnagar Refinery
--	---	---	---

Electromagnetic Flowmeter

Model: FlowMag S630-Ex | Tag: FT-201A | Qty: 2 Nos. | Line Size: 150NB

1. GENERAL ASSEMBLY DRAWING (G.A.D.)

GENERAL ARRANGEMENT DRAWING (G.A.D.)

Insert approved AutoCAD / SolidWorks drawing here

Drawing No: FT-GAD-SO-2026-0542-01

Revision: Rev. 0

Product: Electromagnetic Flowmeter

Line Size: 150NB

Scale: As noted on drawing

Projection: Third Angle

2. GENERAL SPECIFICATIONS			
Manufacturer	Flowtech Measuring Instruments Pvt. Ltd., India	SO / PO Reference	SO-2026-0542
Product Description	Electromagnetic Flowmeter	Model / Type	FlowMag S630-Ex
Tag Number	FT-201A	Line / Equipment No.	6"-WLI-201A-01
Quantity	2 Nos.	Project	Jamnagar Refinery Expansion

3. PROCESS CONDITIONS

Service / Fluid	Demineralised Water	Operating Flow (Min)	50 m³/hr
Operating Flow (Max)	500 m³/hr	Operating Pressure	6 bar g
Operating Temperature	45°C	Design Pressure	10 bar g
Design Temperature	80°C	Density	998 kg/m³
Viscosity	0.8 cP	Specific Gravity	0.998
Conductivity	> 50 uS/cm	Line Size	150NB

4. MECHANICAL SPECIFICATIONS

Process Connection	Flanged	Connection Rating	PN16
Flange Standard	IS 6392 / ANSI B16.5	Face-to-Face	As per manufacturer std.
Mounting Orientation	Horizontal	Overall Length	As per G.A.D.

5. MATERIALS OF CONSTRUCTION (M.O.C.)

Body / Housing	SS 316	Flange / End Fitting	SS 316
Liner / Lining	PTFE	Electrodes	SS 316L
Sensor / Transducer	SS 316L / Hastelloy C	Gaskets	PTFE / CAF
Bolts & Nuts	SS 304	Cable Glands	2 x M20 x 1.5

6. ELECTRICAL SPECIFICATIONS

Output Signal	4-20 mA + HART	Power Supply	24 VDC (2-wire loop)
Communication	HART 7.0	Enclosure Protection	IP66 / IP67 / NEMA 4X
Haz. Area Cert.	Ex d IIC T6 Gb	EMC Compliance	IEC 61326-1
Ambient Temp.	-40 to +60°C	Display	LCD with backlight

7. PERFORMANCE SPECIFICATIONS

Accuracy	±0.5% of reading	Repeatability	±0.1% of reading
Turndown Ratio	10:1	Response Time	< 100 ms
Span Adjustment	Zero: ±50% / Span: ±50%	Calibration Cert.	ISO 17025 traceable

8. ACCESSORIES & OPTIONS

Sr.	Accessory / Option	Qty	Specification
1	2-valve / 3-valve / 5-valve Manifold	—	SS 316, rated to process pressure
2	Mounting Bracket (Pipe / Wall)	—	SS 304 / CS epoxy coated
3	Sun Shade / Weather Protection	—	SS 304, IP66

9. SCOPE OF SUPPLY & DOCUMENTATION

- ☒ Instrument (as specified) ☒ Calibration Certificate (ISO 17025) ☒ Material Test Certificate (EN 10204 3.1)
☒ Hydrostatic Test Certificate ☒ O&M Manual ☒ G.A.D. + Q.A.P.

10. APPLICABLE STANDARDS & CERTIFICATIONS

Standard Type	Reference
Quality Management	ISO 9001:2015 Certified
Explosion Protection	IEC 60079-0, IEC 60079-1, IEC 60079-11
IP Rating	IEC 60529 -- IP66 / IP67 / NEMA 4X

11. COMMERCIAL TERMS

Delivery Period	6-8 weeks	Packing	Wooden box + polythene wrapping
Warranty	18 months	Freight	Ex-works Vadodara, Gujarat

Special Requirements / Notes: Third party inspection by TÜV SÜD required. PESO flameproof certification mandatory.

12. AUTHORISATION & SIGNATURES

Prepared by: _____ Design Engineer Date: _____	Checked by: _____ Project Manager Date: _____	Approved by: _____ Customer / Consultant Date: _____ Stamp: _____
--	---	---